



# MicroCom DXI

SAC-110

Service, Administration, and Control Computer

## Description

The SAC-110 is the rack mount version of the MicroComm DXI Service, Administration, and Control (SAC) computer. Each SAC computer (or optional hot standby redundant SAC computer pair) controls a MicroComm DXI exchange. Up to twenty exchanges can be connected to form a MicroComm DXI system. Virtually all MicroComm DXI operating functions can be externally controlled through its dedicated host port networks and common protocol

The SAC computer is an IBM PC compatible computer with the following minimum requirements:

- x86 compatible CPU
- 1 GB Hard Drive (or higher)
- video card
- ethernet port
- modem
- exchange data network card
- two serial ports
- QNX 4.X operating system
- MicroComm DXI system software

## Features

- maintenance test routines for testing I/O boards in conjunction with board test modules
- on-line modification of system configuration data
- pairs of SAC computer may be configured for 'hot standby' redundant operation
- redundant SAC computers can be operated from a single keyboard and monitor with keyboard/monitor switch
- Ethernet SAC data network communications
- LonWorks exchange data network communications
- Ethernet and other various host port communications networks
- logging and on demand printing of all system activity
- user and maintenance levels of log display
- factory service assistance via modem/ethernet



## Specifications

|                       |  |
|-----------------------|--|
| Physical              |  |
| CPU Case              | 4U 19" rack mount<br>16.6" W x 6.9"H x 23.5" D<br>(422 x 176 x 596 mm)     |
| Environmental         |  |
| Operating Temperature | 32 to 113 °F (0 to 45 °C)  |
| Storage Temperature   | 32 to 122 °F (0 to 50 °C)  |
| Humidity              | 0 to 95 % non-condensing   |
| Power Supply          | nominal 110 VAC 5 A max<br>standard 6 ft AC power cord                     |
| Standards             | FCC Part 15, UL, CSA   |
| Other                 | standard IBM PC compatible<br>serial, parallel, VGA, and keyboard<br>ports |

## Ordering Information

Part Number SAC-110-ABC-DEF

- A Computer Case Options
  - 1 rack mount
  - 2 rack mount (2 unit - limited options)
  - 3 rack mount with CD audio output
  - 5 rack mount with ISA slots
  - 6 rack mount with ISA slots and CD output
- B Card 1 options
  - 0 no card
  - 1 1 direct connect o/p (no longer available)
  - 2 1 direct connect + 1 FTT o/p (no longer available)
  - 3 1 FTT o/p (no longer available)
  - 4 2 FTT o/p (no longer available)
  - 5 1 FTT o/p - PCI Card
- C Card 2 options
  - 0 no card
  - 1 1 direct connect o/p (no longer available)
  - 2 1 direct connect + 1 FTT o/p (no longer available)
  - 3 1 FTT o/p (no longer available)
  - 4 2 FTT o/p (no longer available)
  - 5 1 FTT o/p - PCI Card
- D Ethernet options
  - 0 none
  - 1 Silver Streak (no longer available)
  - 2 AUI (no longer available)
  - 3 10/100 base T (standard)
  - 4 10 base 2 (no longer available)
  - 5 FOIRL (no longer available)

- E Modem options
  - 0 none
  - 1 internal
- F Other cards
  - 0 none
  - 3 Ethernet 10/100 base T (2 total)
  - 4 two Ethernet 10/100 base T (3 total)
  - 9 specify

## Replacement Hard Drives

Part Number HDR-100 SAC IDE PATA Hard Drive \*

Part Number HDR-103 SAC IDE SATA Hard Drive \*

\* Contact the factory to arrange for pre configuration of hard drives

## Accessories

LCD keyboard/monitor

keyboard/monitor switch

