


Axis^{AX}

8-Way Relay Output Card

The AX-RL8 8-Way Relay Output Card is an internal peripheral card for use with Advanced Axis AX fire alarm control panels. The AX-RL8 card provides 2 Form-C and 6 Form-A (normally open) freely programmable relay contacts. Communications of the card and relays are done via a flat ribbon cable connection to the AX-CTL base card.

Compatible with the Axis AX Series Dynamix I/O relationship programming, the relays of the AX-RL8 can be individually assigned to any input or output relationship, output group, timing function, gated function, invert operation etc to perform project-specific control operations. To simplify installation, each AX-RL8 relay output is pre-configured to activate on a common alarm.

Ideally suitable for elevator control, HVAC shutdown, door holder release, or similar ancillary functions, each AX-RL8 relay is rated 30 VDC/VAC @ 1 Amp with a PF rating of 1 (resistive).




Features

- Eight (8) Individually Programmable Relays
- Contacts Rated 30 VDC/VAC, 1 Amp (Resistive)
- 2 Form-C and 6 Form-A Relays
- Fail-Safe Programmable
- Programmable Silenceable or Non-Silenceable
- Cost-Effective Ancillary Output
- Programmable Timing Functions
- Supports Dynamix I/O Relationship Programming
- Removable Field Wiring Terminal Blocks
- Rapid Activation Response

Listings and Approvals

- Certified to UL864 10th Edition – File No. S35979
- CSFM Approved: Pending
- NYCFD COA: Pending

Wiring Diagram



AX-RL8 (8-Way Relay Output Card)

Specification

Relay Outputs	2 Form-C and 6 Form-A (Normally Open)
Relay Output Ratings	30 VDC/VAC @ 1 Amp, PF-1 (Resistive)
Operating Voltage	18-28 VDC (From Axis AX Series Base Card)
Operating Current	
Quiescent	0 mA
Alarm	65 mA (All Relays On)
Environment	Indoor, Dry
Operating Temperature	32 °F-120 °F (0 °C-48 °C)
Humidity	10%-95% (Non Condensing)
Dimensions	2.76" X 4.13" X 0.71"
Weight	2.5 oz

Order Codes and Options

AX-RL8	8-Way Relay Output Card
521-194	10-Pin Flat Ribbon Cable, Replacement

Check if this document is up to date | Give us feedback

9564 Yellowhead Trail NW, Edmonton AB, T5G 0W4, Canada T: 1 (866) 462-7100 E: info@harding-tech.com W: www.harding-tech.com

As our policy is one of constant product improvement the right is therefore reserved to modify product specifications without prior notice.