

Description

TITANUS® aspirating smoke detector

The TITANUS® family of aspirating smoke detectors covers standard to very early warning fire detection as well as a wide range of extreme applications without compromising high levels of sensitivity and performance.

Technology

TITANUS *TOP-SENS*® aspirating smoke detection system combines High-Power-Light-Source (HPLS) technology with patented LOGIC·SENSTM fire pattern recognition algorithms and a large portfolio of custom accessories to ensure that each system will maintain high levels of sensitivity and false alarm immunity even in challenging environments. Its modular design facilitates cost effective solutions for a wide range of specialized requirements. Optional second plug-in detector module allows one aspirating unit to economically monitor two separate areas or alternatively to be used for cross-zoning alarm verification. TITANUS *TOP-SENS*® comes with dry contacts for connection to any fire panel as well as free slots for inserting bus modules.

Advantages

- Modular design for cost effective solutions to fit the needs on site.
- High reliability and extended service life due to physical separation of disturbing influences such as dust, vapor or radiation from the measuring chamber.
- TITANUS® PipeXpress software for highly reliable ASD planning with just a few mouse clicks.
- Time-saving Installation and commissioning thanks to plug & play philosophy.
- Discreet installation for maintaining aesthetics and providing safety against vandalism.
- Intelligent diagnostics tool gives support at inspection and service.



Features

- System coverage up to 64,560 ft² (6,000 m²) or rather 32,280 ft² (3,000 m²) per detector module
- High-Power-Light-Source (HPLS) for standard to very high sensitivity
- LOGIC·SENSTM for very high immunity to false alarms
- PIPE·GUARD patented air flow monitoring system, sensing changes in total airflow as little as +/-10 %
- Optional 2nd detector module for cross-zoning alarm verification or increased area of coverage
- Up to 984 ft (300 m) pipe length and up to 100 holes per detector module
- Designed for harsh environments, with a wide range of accessories for special applications
- 3 alarm levels per detector module for tiered alerting
- Bar graph smoke level display
- Optional Ethernet (TCP/IP) / SNMP / data logger
- Operating temperature: -4 °F to +140 °F (-20 °C to +60 °C) depending on version
- Also available as TITANUS *TOP-SENS*® cold storage version

Listing

UL Standard
FM Approved
VdS Approved

• Document # DS-DM-TT-1.0 • Copyright © 2021 Harding Instruments Co. Ltd. • All Specifications are subject to change without notice • Printed in Canada



9564 Yellowhead Trail NW Tel 780.462.7100
Edmonton, Alberta, T5G 0W4 Fax 780.450.8396
sales@harding-tech.com www.harding-tech.com



Represented by:



Aspirating Smoke Detector

TITANUS TOP-SENS - Standard and Silent Version

Devices

TITANUS TOP-SENS

System	TITANUS TOP-SENS Standard Version	TITANUS TOP-SENS SILENT Version
Basic Device		
Type	TT-1-U	TT-1-SL-U
Max Main Alarm Sensitivity	0.005% obsc./ft (0.015% obsc./m)	
No. of Detector Modules (Zones)	1 or 2	
Max. No of Aspirating Holes	2 x 63	1 x 100 or 2 x 72
Max Area Coverage	64,560 sq. ft. (6,000 sq. m.) per system / 32, 280 sq. ft. (3,000 sq. m.) per zone	
Max Pipe Length	1 x 980 ft (1 x 300 m) per zone	
Cross Zoning Alarm Verification	Optional with 2 nd Detector Module	
No. of Alarm Levels per Zone	3	
No. of Output Relays (1 A/ 30 VDC)	8 Relays (changeover/form C)	
Front Indicator	Fault; Operation; per Zone: 3 x Alarm, 1 Bar Graph (Smoke Level)	
Ethernet/SNMP/ Data Logger (SD Card)	Optional	
Binary Data Logger	Standard	
Supply Voltage	24 VDC (14 to 30 VDC)	
Current Consumption min. Operational (1 Detector Module, 24 VDC) Alarm	200mA 230mA	150mA 180mA
Current Consumption min. Operation (2 Detector Module, 24 VDC) Alarm	230mA 290mA	190mA 220mA
Operating Temperature	-4 °F to +140 °F (-20 °C to +60 °C)	+32 °F to +104 °F (0 °C bis +40 °C)
Humidity Range	10 % to 95 % (noncondensing)	
Sound Pressure Level (ISO 3744)	as low as 45 dB(A)	as low as 23 dB(A)
Dimensions	4.5 x 7.9 x 11.5 inches (113 x 200 x 292 mm)	
Weight (Basic Configuration)	3.0 lbs + 0.22 lbs (1,350 g + 100 g) per detector module	
Pipe Specification	63 / 64 inches (25 mm)	
IP Rating	standard: IP 20 / optional: IP 52	

Detector Modules

Type	DM-TT-50-L-U	DM-TT-10-L-U	DM-TT-01-L-U
Weight		0.22 lbs (100g)	
Sensitivity Rating	Standard	Medium	High
Max. Main Alarm Sensitivity	0.15% obsc./ft (0.5% obsc. ft)	0.03% obsc. /ft (0.10% obsc. / m)	0.005% obsc. /ft (0.015% obsc. /m)

Adhesive Front Film Sheet

Using 1 (2) Detector Modules, Type	FW-TT-1 (FW-TT-2; for indicating external shutdown: FW-TT-3)
------------------------------------	--

Fan Controller Type FC-3 required for more than 63 holes per detector module

2 Network Module with (without) Data Logger: NU-5-D (NU-5); Data Logger only: NU-5-DO

3 As low as 31 dB (A) without sound absorber type SD-1

- Document # DS-DM-TT-1.0
- Copyright © 2021 Harding Instruments Co. Ltd.
- All Specifications are subject to change without notice
- Printed in Canada



9564 Yellowhead Trail NW
Edmonton, Alberta, T5G 0W4
sales@harding-tech.com

Tel 780.462.7100
Fax 780.450.8396
www.harding-tech.com



Represented by: