

## Description

The ELUXA horns, horn strobes, and strobes feature an advanced power saving LED technology with a full range of low and high candela settings for indoor wall and ceiling-mount applications. Designed in sleek, modern enclosures, ELUXA's aesthetically pleasing low profile will blend with the building's interior décor.

## Low Profile Design and Rich Feature Set

With the industry's smallest footprint, the ELUXA horns are aesthetically pleasing to building owners as the low-profile design does not detract from the interior decor. ELUXA is feature rich 3 horn patterns (Continuous, T3, T3/T4) in 1 device, pre-wire/pre-test via mounting plate with hinged feature for ease-of-installation, single-gang design (wall models), and no tools needed for setting changes. The ELHN horn are for 24V operation. ELHN is suitable for 12V applications.

## Approvals and synchronization

The ELUXA notification appliances are listed under UL Standards 1971, 1638, and 464 and under CAN/ULC-S525 and CAN/ULC-S526. The appliances are Restriction of Hazardous Substances (RoHS) compliant and contain no mercury or other hazardous substances. In addition, the ELUXA product line has been UL/ULC listed as compatible with all Fire Alarm Control Panels (FACP) and accessories that have been determined to be compatible with Exceder LED3 and Wheelock RSS strobe-based products including the RSS, CH, E, EH, ET, ST, HS, MT, S8, SA, STH and Z Series. The listing also includes the ability to install the ELUXA strobes in the same notification zone and field of view with any Wheelock RSS and Exceder LED3 strobe models.



## Features

- One of the smallest, most compact single-gang designs
- Sleek, modern aesthetics with no visible mounting screws
- Special lettering available
- 3 horn patterns (Continuous, T3, and T3/T4; Fire and CO signaling in 1 device)
- Sound pressure (Anechoic) dBA
- Low 86, High 91 (for Continuous, T3, and T4)
- Easy-to-install
- Mounting plate included with all models: Convenient capture hinge allows installers to easily hold the device while fastening the single-mount screw in place.
- Pre-wire/pre-test capability to check for wiring and ground faults prior to appliance installation
- Finger slide switches--No tools needed for setting changes
- IN/OUT screw terminals using #12 to #18 AWG wires
- Mounting options include ELSBB, any single-gang backbox and to 4" square with adapter kit for wall models and LSPKBB-C backboxes, 4" square, 1 1/2" or 2 1/8" deep and 4" Octagonal, 1 1/2" or 2 1/8" deep for ceiling models
- Meet synchronizing standards with Wheelock's DSM Sync Modules, PS Power Supplies or SAFEPTH products
- Compliance
  - UL 1971, UL 1638, UL 464, ULC-S525, ULC-S526
  - California State Fire Marshal (CSFM)
  - RoHS
  - FCC Part 15, ICES

• Document # DS-ELHN-1.0    • Copyright © 2021 Harding Instruments Co. Ltd.    • All Specifications are subject to change without notice    • Printed in Canada



9564 Yellowhead Trail NW    Tel 780.462.7100  
Edmonton, Alberta, T5G 0W4    Fax 780.450.8396  
[sales@harding-tech.com](mailto:sales@harding-tech.com)    [www.harding-tech.com](http://www.harding-tech.com)



Represented by:



**Specifications**

| Model      | Regulated Voltage Range (VDC) | High dB | Low dB |
|------------|-------------------------------|---------|--------|
| ELHN/ELHNC | 8.0-17.5                      | 0.025   | 0.020  |
| ELHN/ELHNC | 16.0-33.0                     | 0.028   | 0.021  |

| Model  | Mounting | Red | White | Lettering    | Sync w/ DSM or Wheelock Power Supplies |
|--------|----------|-----|-------|--------------|--|
| ELHNR  | Wall     | X   |       | No Lettering | X                                      |
| ELHNW  | Wall     |     | X     | No Lettering | X                                      |
| ELHNRC | Ceiling  | X   |       | No Lettering | X                                      |
| ELHWC  | Ceiling  |     | X     | No Lettering | X                                      |

| Physical               |  |
|------------------------|--|
| Material               | Red or white textured UV stabilized, colored impregnated engineered plastic. Exceeds 94V-0 UL flammability rating  |
| Weight                 | Wall: 0.35 lbs; Ceiling: 0.55 lbs  |
| Dimensions             | Wall: 4.79”H x 2.76” W x 1.18” D, Trimplate: 5.25” H x 4.58” W x 0.32” D; Ceiling: 6.27” Diameter x 1.69” D  |
| Operating Temperatures | Indoor: 32°F to 122°F (0°C to 50°C) and maximum humidity of 93%  |
| Mounting and Wiring    |  |
| Mounting (Indoor Only) | Mounting plate included with all models. ELHN can be used for wall and ceiling-mount applications. Wall mounting: Single-gang, ELSBB backboxes or to 4” square with adapter kit. ELHN can be used for wall and ceiling-mount applications. The ELHNC can also be used for wall-mount applications. Ceiling mounting: LSPKBB-C backboxes or to 4” square, 1 1/2” or 2 1/8” and Octagonal, 1 1/2” or 2 1/8” deep |
| Wiring Connection      | #12 through #18 AWG  |
| Power & General        |  |
| Operating Voltage      | 12 VDC/VFWR: 8 - 17.5 VDC/VFWR; 24 VDC/VFWR: 16 - 33 VDC/VFWR (12 VDC ELHN/ELHNC models only)  |
| Synchronization Models | ELUXA can synchronized with Wheelock’s DSM Sync Modules, PS Power Supplies or SAFEPATH products, using Wheelock patented sync protocol   |

**Engineer’s Specifications**

The LED notification appliances shall be ELHS audible visual strobe appliances, ELST visual strobe appliances and ELHN audible appliances for wall and ceiling-mount applications with a low-profile design or approved equals. Special lettering, including AGENT, ALERT, EVACUATE, and no lettering, shall be available. The ELHS and ELST strobes shall be listed for UL Standard 1971 (Emergency Devices for the Hearing-Impaired) for Indoor Fire Protection Service and UL 1638 (Visible Signaling Devices). The ELHS and ELHN Audibles shall be UL Listed under Standard 464 (Fire Protective Signaling). All models shall meet the requirements of FCC Part 15 and ICES-003. All inputs shall be compatible with standard reverse polarity supervision of circuit wiring by a Fire Alarm Control Panel (FACP) with the ability to operate from 16 to 33 VDC/VFWR. The ELHS audible strobe and ELST strobe appliances shall produce a flash rate of one (1) flash per second over the Regulated Voltage Range and shall incorporate a Light Emitting Diode (LED) as the light source with a rugged Lexan® lens. The appliances shall be of low current design. The LED strobe flash duration shall be 20 ms. Where Multi-Candela appliances are specified, the strobe intensity shall have 6 field selectable settings at 15, 30, 75, 110, 135 and 185 candela for wall mount applications and 15, 30, 75, 110, 150 and 177 for ceiling applications. The selector switch for selecting the candela shall be tamper resistant. Appliances with candela settings shall show the candela selection in a visible location at all times when installed. The audible shall have a choice of three (3) horn patterns (high & low output): Continuous, T3, and T3/T4 for fire (T3) and CO (T4) signaling. The ELHS audible strobe, ELST strobe, and ELHN audible shall include a hinged mounting plate. Mounting options shall include LED backboxes, single-gang backbox and to 4” square with adapter kit for wall-mount models and LED Ceiling backboxes, 4” square, 1 1/2” or 2 1/8” deep and 4” Octagonal, 1 1/2” or 2 1/8” deep for ceiling models. Two wire appliance wiring shall be capable of directly connecting to the mounting base. Removal of an appliance shall result in a supervision fault condition by the Fire Alarm Control Panel (FACP). All notification appliances shall be backwards compatible. The ELHS, ELHN and ELST wall models shall have a low profile measuring 4.79”H x 2.76” W x 1.18” D. The ELHSC, ELHNC and ELSTC ceiling models shall have a low profile measuring 6.27” Diameter with 1.69” D. When synchronization is required, the appliance shall be compatible with Wheelock®’s DSM Sync Modules, PS Power Supplies, SAFEPATH products or other manufacturer’s panels with built-in Wheelock® Patented Sync Protocol. The strobes shall not drift out of synchronization at any time during operation. If the sync protocol fails to operate, the strobe shall revert to a non-synchronized flash rate and still maintain (1) flash per second over its Regulated Voltage Range. The appliance shall also be designed so that the audible signal may be silenced while maintaining strobe activation when used with Wheelock® patented sync protocol.

NFPA 72 2016, UL 1971, UL, 1638, UL 464 ULC-S525-16, ULC-S526-

16, CSEFM, FCC, RoHS, ICES

- Document # DS-ELHN-1.0
- Copyright © 2021 Harding Instruments Co. Ltd.
- All Specifications are subject to change without notice
- Printed in Canada



9564 Yellowhead Trail NW Tel 780.462.7100  
Edmonton, Alberta, T5G 0W4 Fax 780.450.8396  
[sales@harding-tech.com](mailto:sales@harding-tech.com) [www.harding-tech.com](http://www.harding-tech.com)



Represented by: