

Description

Ideal for mass notification and emergency communications, the ELUXA speaker strobes feature high fidelity sound output and an advanced power saving LED technology with a full range of candela settings for indoor wall and ceiling-mount applications. With the widest frequency response range (300 to 8000 Hz) in the industry, the ELSPST-A/ELSPSTC-A speaker strobes features leading intelligibility with crisp, clear voice messages and tone signaling. Special lettering for the colored lens speaker strobes includes "ALERT" and no lettering.

High efficiency, LED technology

ELUXA's high energy efficient technology leads the industry in lowest current draw across the full candela range, which reduces overall power consumption and costs in fire alarm systems. As the first notification appliances in the industry to utilize LED as the light source, this breakthrough and patented optical design, resulting in best-in-class efficiency, enables material and system cost savings, allowing for a greater number of appliances on the notification appliance circuit and fewer power supplies. All strobe models feature six candela settings: 15, 30, 75, 110, 135, 185 cd on wall models and 15, 30, 75, 110, 150, 177 cd on ceiling models

Low profile design and rich feature set

With the industry's smallest footprint, the ELUXA amber lens speaker strobes are aesthetically pleasing to building owners as the low-profile design does not detract from the interior decor. ELUXA is feature rich with 6 candela settings in 1 device, dual voltage (25/70 VRMS) capability, field selectable taps from 1/8 to 2 watts (5W - 70V), pre-wire/pre-test via mounting plate with hinged feature for ease-of-installation, and no tools needed for setting changes. These products are suitable for indoor wall and ceiling mount applications. The ELSPST speaker strobes are 24V operation.

Approvals and synchronization

Eaton's ELUXA strobes meet the 20-millisecond light pulse duration requirements of the 2016 edition of NFPA 72. By meeting this latest requirement, xenon and LED devices can now be in the same field of view. The ELUXA notification appliances are listed under UL Standards 1638 and 1480 and under CAN/ULC-S526 and CAN/ULC-S541. The appliances are Restriction of Hazardous Substances (RoHS) compliant and contain no mercury or other hazardous substances.

In addition, the ELUXA product line has been UL/ULC listed as compatible with all Fire Alarm Control Panels (FACP) and accessories that have been determined to be compatible with Exceder LED3 and Wheelock RSS strobe-based products including the RSS, CH, E, EH, ET, ST, HS, MT, S8, SA, STH and Z Series. The listing also includes the ability to install the ELUXA strobes in the same notification zone and field of view with any Wheelock RSS strobe and Exceder LED3 models.



Features

- High Fidelity Sound Output High intelligibility at minimum wattage across a frequency range of 300 to 8000 Hz
- Energy Efficient LED technology provides industry's lowest current draw
- Fewer power supplies required, smaller wire gage, reduced wire runs
- Low-Profile Design Smallest footprint with sleek, modern aesthetics
- Special Lettering Available
- Field Selectable Settings in 1 Device Wall: 15, 30, 75, 110, 135, 185 cd
- Ceiling: 15, 30, 75, 110, 150, 177 cd
- Field Selectable Taps 1/8 watt up to 2 watts (5W - 70V)
- 25 or 70 VRMS operation
- Easy-to-Install Mounting plate included with all models: Convenient capture hinge allows installers to easily hold the device while fastening the single-mount screw in place.
- Pre-wire/pre-test capability to check for wiring and ground faults prior to appliance installation
- Finger slide switches--No tools needed for setting changes
- Built-in level adjustment feature and Snap-On grille cover
- IN/OUT screw terminals using #12 to #18 AWG wires
- Mounting Options include ELUXA ELSPKBB backboxes and 4" square, 2 1/8" deep backboxes for wall models and LSPKBB-C backboxes, 4" square, 1 1/2" or 2 1/8" deep and 4" Octagonal, 1 1/2" or 2 1/8" deep for ceiling models
- Strobe Synchronization Components Meet synchronizing standards with Wheelock's DSM Sync Modules, PS Power Supplies or SAFEPATH products
- Ability to mix xenon and LED strobes in the same field of view
- Compliance NFPA 72 2016 - 20 ms flash duration requirements
- UL 1480, UL 1971 Light Distribution (Amber lens), UL 1638 (Amber Lens), ULC-S541, ULC-S526
- California State Fire Marshal (CSFM)
- ADA/NFPA/ANSI/OSHA

- Document # DS-ELST-1.0
- Copyright © 2021 Harding Instruments Co. Ltd.
- All Specifications are subject to change without notice
- Printed in Canada



9564 Yellowhead Trail NW Tel 780.462.7100
Edmonton, Alberta, T5G 0W4 Fax 780.450.8396
sales@harding-tech.com www.harding-tech.com



Represented by:



ELUXA Speaker Strobes

ELSPST Devices

Specifications

Model	Regulated Voltage Range (VDC)	UL/ ULC Max Current - 24 VDC							
		15	30	75	110	135	150	177	185
ELSPST	16.0-33.0	0.022	0.030	0.060	0.086	0.125			0.185
ELSPSTC	16.0-33.0	0.022	0.030	0.060	0.086		0.125	0.185	

Model	UL Reverberant dBA at 10 ft					Anechoic dBA per CAN/ULC-S541-07				
	1/8 Watts	1/4 Watts	1/2 Watts	1 Watts	2 Watts (5W-70V)	1/8 Watts	1/4 Watts	1/2 Watts	1 Watts	2 Watts (5W-70V)
ELSPST Speaker Strobe	75	79	82	85	87	75	79	82	85	87

Model	Mounting	Strobe Candela	Red	White	Lettering	Sync w/ DSM or Wheelock Power Supplies
ELSPSTR-ALA	Wall	15/30/75/110/135/185	X		ALERT	X
ELSPSTW-ALA	Wall	15/30/75/110/135/185		X	ALERT	X
ELSPSTW-NA	Wall	15/30/75/110/135/185		X	NO LTR	X
ELSPSTR-NA	Wall	15/30/75/110/135/185	X		NO LTR	X
ELSPSTWC-ALA	Ceiling	15/30/75/110/150/177		X	ALERT	X
ELSPSTRC-ALA	Ceiling	15/30/75/110/150/177	X		ALERT	X
ELSPSTWC-NA	Ceiling	15/30/75/110/150/177		X	NO LTR	X
ELSPSTRC-NA	Ceiling	15/30/75/110/150/177	X		NO LTR	X

Physical	
Material	Red or white textured UV stabilized, colored impregnated engineered plastic. Exceeds 94V-0 UL flammability rating
Weight	Wall Speaker Strobe: 1.54 lbs (700g); Ceiling Speaker Strobe: 1.54 lbs (700g); Speaker Backbox: .44 lb (200g)
Lens	Light Emitting Diode (LED) in a rugged Lexan lens
Dimensions	ELSPST: 6.35"H x 4.56" W x 1.54"; ELSPSTC: 6.27" Diameter x 2.29" Depth
Operating Temperatures	Indoor: 32°F to 122°F (0°C to 50°C) and maximum humidity of 93%
Mounting and Wiring	
Mounting (Indoor Only)	Mounting plate included with all models. ELSPST speaker strobes are for wall-mount applications only. Mounting to ELUXA ELSPKBB backboxes or to 4" square 2 1/8" deep backboxes. ELSPSTC speaker strobes are for ceiling-mount applications only. Exceeder LSPKBB-C backboxes and to 4" square, 2 1/8" deep backboxes.
Wiring Connection	#12 through #18 AWG
Power & General	
Operating Voltage	25/70 VRMS; Strobe: 24VDC/24VFWR
Strobe Output	UL 1971, UL 1638, ULC S526: Selectable 15, 30, 75, 110, 135, 185 candela output for wall models; Selectable 15, 30, 75, 110, 150, 177 candela output for ceiling models
Synchronization Models	ELUXA can synchronized with Wheelock's DSM Sync Modules, PS Power Supplies or SAFEPATH products, using Wheelock patented sync protocol
Frequency Range	300 Hz to 8000 Hz
Strobe Flash Rate	Strobes are designed to flash at 1 flash per second

• Document # DS-ELST-1.0 • Copyright © 2021 Harding Instruments Co. Ltd. • All Specifications are subject to change without notice • Printed in Canada



9564 Yellowhead Trail NW
Edmonton, Alberta, T5G 0W4
sales@harding-tech.com

Tel 780.462.7100
Fax 780.450.8396
www.harding-tech.com



Represented by:



Engineer's Specifications

speaker strobe appliances shall be Eluxa ELSPST-A amber lens speaker strobes for wall-mount applications and Eluxa ELSPSTC-A for ceiling mount applications or approved equals. Special lettering for the amber lens speaker strobes shall include "ALERT" and no lettering. The speakers shall be UL Listed under UL 1480 for Fire Protective Service and speakers equipped with strobes shall be listed under UL 1638 for visual signaling appliances - Private Mode with the light distribution meeting UL 1971 light output. In addition, the speaker strobes shall meet the requirements of FCC Part 15 and ICES-003. All inputs shall be compatible with standard reverse polarity supervision of circuit wiring by a Fire Alarm Control Panel (FACP) with the ability to operate from 16 to 33 VDC. All speaker strobes shall be designed for a field selectable input of either 25 or 70 VRMS, with selectable power taps from 1/8 watt to 2 watts and 5 watts for 70V. All models shall have listed sound output of up to 87 dB at 10 feet and a listed frequency response of 300 to 8000 Hz. All inputs shall employ terminals that accept #12 to #18 AWG wire sizes. The ELSPST speaker strobe appliances shall produce a flash rate of one (1) flash per second over the Regulated Voltage Range and shall incorporate a Light Emitting Diode (LED) as the light source with a rugged Lexan® lens. The series shall be of low current design. The LED strobe flash duration shall be 20 ms. The strobe shall include 6 field selectable settings at 15, 30, 75, 110, 135 and 185 candela for wall mount applications and 15, 30, 75, 110, 150 and 177 for ceiling mount applications. The selector switch for selecting the candela shall be tamper resistant. Appliances with candela settings shall show the candela selection in a visible location at all times when installed. The speaker strobe shall be available with clear or amber lens. The series ELSPK and ELSPST shall be designed for indoor surface or flush mounting and include a mounting plate. Mounting options for wall shall include Eluxa speaker backboxes and to standard 4" square, 2 1/8" deep backboxes. Mounting options for ceiling shall include Exceder LED ceiling backboxes, 4" square, 1 1/2" or 2 1/8" deep and 4" Octagonal, 1 1/2" or 2 1/8" deep. The speaker and speaker strobe shall incorporate a speaker mounting plate with a snap-on grille cover and shall mount to standard electrical hardware requiring no additional trimplate or adapter. Removal of an appliance shall result in a supervision fault condition by the Fire Alarm Control Panel (FACP). All notification appliances shall be backwards compatible. The ELSPST wall model shall have a low profile measuring 6.35" H x 4.56" W x 1.54" D. The ELSPSTC ceiling models shall have a low profile measuring 6.27" diameter with 2.29"D. Finish shall be red or white. When synchronization is required, the appliance shall be compatible with Wheelock's DSM Sync Modules, PS Power Supplies, SAFEPATH products or other manufacturer's panels with built-in Wheelock Patented Sync Protocol. The strobes shall not drift out of synchronization at any time during operation. If the sync protocol fails to operate, the strobe shall revert to a non-synchronized flashrate and still maintain (1) flash per second over its Regulated Voltage Range.

UL 1480, UL 1971 Light Distribution (Amber lens), UL 1638 (Amber Lens), ULC-S541, ULC S526, CSFM, FCC, ICES

- Document # DS-ELST-1.0
- Copyright © 2021 Harding Instruments Co. Ltd.
- All Specifications are subject to change without notice
- Printed in Canada



9564 Yellowhead Trail NW
Edmonton, Alberta, T5G 0W4
sales@harding-tech.com
Tel 780.462.7100
Fax 780.450.8396
www.harding-tech.com



Represented by: